

(12) UK Patent Application (19) GB (11) 2 330 157 (13) A

(43) Date of A Publication 14.04.1999

(21) Application No 9721258.3

(22) Date of Filing 07.10.1997

(71) Applicant(s)
Bluewater Terminal Systems N.V.
(Incorporated in the Netherlands Antilles)
Zeelandia Office Park, Kaya W.F.G.(Jombi)Mensing 18,
Willemstad, Curacao, Netherlands Antilles

(72) Inventor(s)
Jacob de Baan

(74) Agent and/or Address for Service
Bout Wade Tennant
27 Furnival Street, LONDON, EC4A 1PQ,
United Kingdom

(51) INT CL⁶
E21B 17/01 43/01

(52) UK CL (Edition Q)
E1F FAC FAC1

(56) Documents Cited
GB 2296904 A GB 2206144 A US 4906137 A

(58) Field of Search
UK CL (Edition P) E1F FAC
INT CL⁶ E21B
Online: WPI

(54) Abstract Title
Riser system for connecting a seabed installation with a floating vessel

(57) A riser system for connecting a seabed installation to a floating vessel consists of first and second fluid conveying conduits (13,14) connected by an articulated joint (7). In a standby condition the articulated joint (7) is anchored to the seabed, the two conduits (13,14) are not in fluid communication with one another and the upper conduit (13) rises substantially vertically with the aid of a buoyancy device (9). In use, the upper conduit (13) is pulled in to a floating vessel, thereby releasing the articulated joint (7) from the anchor (8) and allowing the joint to pivot in order to connect the upper and lower conduits (13,14) to allow passage of fluid therethrough.






FIG. 1.



2/6

FIG. 2.






FIG. 3a.



3/6

FIG. 3b.



4/6

FIG. 4.




FIG. 5.






FIG. 6a.



RISER SYSTEM FOR CONNECTING A SEABED
INSTALLATION WITH A FLOATING VESSEL

5 The present invention relates to a riser system
used to convey fluids between a seabed installation
such as an oil well and a floating production vessel
on the sea surface.

10 As oil production is moved into ever deeper
waters in search of new fields, the need to have more
robust riser systems which connect the floating
production vessels to the seafloor increases. This
robustness pertains to factors such as the need for
15 large diameter pipes capable of withstanding high
pressures and providing extremely high thermal
insulation properties.

20 A possible solution is the use of double walled
steel pipes, in which the inner pipe conveys the well
fluids while the outer pipe contributes to the thermal
efficiency by allowing an air gap between the two pipe
walls. This type of pipeline has been applied in the
oil industry in static applications and is now also
25 being considered for dynamic applications, i.e those
in which the pipeline is directly suspended from a
floating production vessel.

30 A major drawback with the application of dynamic
steel pipe risers is that the installation of these
risers can only be done once the production vessel is
in the appropriate location. This means that such
installation works are on the critical path to oil
production in terms of schedule and hence have a
negative impact on the economic application of such
35 dynamic risers.

This drawback is primarily due to the fact that the riser geometry does not allow bending radii below a certain limit and to control these radii it is essential for the top of the riser to be continuously supported. Hence, there is the need for the production vessel to be anchored on site to receive and support the riser as the latter is installed.

It is the objective of the present invention to provide an apparatus and method which allows a dynamic riser to be installed prior to the arrival of a production vessel and to effectively abandon the riser in a standby condition until such time as the production vessel is anchored in the field. At that point, only a simple pull-in operation is then required to secure the connection between the vessel and the riser.

The invention reduces the time to production to a matter of days rather than weeks and avoids the need to mobilise an installation vessel which would otherwise be required to install the riser in the close vicinity to the production vessel.

Accordingly, the present invention provides a riser system for connecting a seabed installation to a floating vessel, comprising a first conduit for conveying fluid and which is attachable at a first end to a seabed installation and comprises connector means at a second end, a second conduit for conveying fluid and which is attachable at a first end to a floating vessel and comprises connector means at a second end which is engageable with the connector means of the first conduit to allow fluid communication between the first and second conduits, articulation means joining

the first and second conduits to allow relative rotation therebetween about a pivot axis whereby the first and second conduits are movable into alignment with one another to allow mating engagement of the
5 respective connector means and out of alignment with one another to allow disengagement of the respective connector means.

10 Preferably, the system further comprises anchor means operable to anchor the articulation means adjacent the seabed.

15 The anchor means may comprise a seabed installation which is releasably engageable with the first or second conduit.

20 Alternatively, the anchor means may comprise a ballast weight which is releasably attached to the articulation means.

25 In this case, the ballast weight is preferably secured to the articulation means at a location displaced from the pivot point.

30 Conveniently, buoyancy means is secured to the first end of the second conduit to allow it to float in a substantially vertical position above the anchor means.

35 Buoyancy means may also be secured to the first conduit between its first and second ends.

Conveniently, actuator means may be provided which is operable to cause relative rotation of the first and second conduits about the pivot axis. This

actuator means may comprise a hydraulic ram.

Both the first and second conduits may consist of double skinned pipes.

5

In another aspect of the invention, there is provided a method of assembling a riser system for connecting a seabed installation with a floating vessel comprising the steps of:

- 10 a) providing first and second conduits each having first and second ends;
- b) providing mating connector means at the respective second ends of the first and second conduits;
- 15 c) providing articulation means joining said first and second conduits adjacent said second ends to allow relative rotation about a pivot axis whereby the first and second conduits are movable into alignment with one another to allow mating engagement of the respective connector means and out of alignment with another to allow disengagement of the respective connector means; and
- 20 d) attaching the first end of the first conduit to a seabed installation.
- 25

Preferably the method further comprises step of anchoring the articulation means adjacent the seabed with anchor means.

30

The method may also comprise the step of providing buoyancy means at the first end of the second conduit to allow the second conduit to float in a substantially vertical position above the anchor

35

means.

5 Conveniently, the method further comprises the step of raising the first end of the second conduit to overcome said anchor means and to allow pivoting about the pivot axis to bring the connector means into mating engagement, and securing the first end of the second conduit to a floating vessel.

10 In one embodiment, the anchoring means is releasably engageable with the first or second conduit or the articulation means and the step of overcoming the anchor means comprises disengaging the respective conduit or the articulation means from the anchor
15 means.

 Ideally, the first and second conduits are dimensioned such that the articulation means is located at between 50% and 95% of the water depth
20 below sea level.

 The method may involve providing buoyancy means on the first conduit between the first and second ends.

25 The method may also include providing actuator means operable to assist relative rotation of the first and second conduits about the pivot axis.

30

 The invention will now be described in detail, by way of example only, with the reference to the accompanying drawings in which:

35

FIGURE 1 show a prior art arrangement of a dynamic riser;

FIGURE 1a is a detail of Figure 1 showing a typical double skinned riser pipe;

5 FIGURE 2 shows a dynamic riser arrangement in accordance with the present invention;

FIGURE 3a shows the riser arrangement of Figure 2 installed in the standby condition awaiting arrival of a production vessel;

10 FIGURE 3b shows an alternative configuration of the riser arrangement of Figure 3a;

FIGURE 4 shows the stages whereby the riser system of Figure 3 is moved from the standby position into connection with a production vessel;

15 FIGURE 5 is a first embodiment of articulation means provided in the riser;

FIGURE 6 is a second embodiment of articulation means provided in the riser; and

20 FIGURE 6a is a view of the anchoring arrangement of Figure 6 in a direction indicated by arrow A.

Figure 1 shows a conventional dynamic riser layout. A production vessel 1 floating on the sea surface is shown supporting one riser 2, although in practice the vessel usually supports five to ten risers at the same time. The riser 2 extends in a generally catenary configuration to the seabed 3 where it is connected to a production well (not shown). However, conventional buoyancy aids 4 may be provided on the lower portion of the riser 2 as shown.

25

30

As the detailed view in Figure 1a illustrates,
the riser 2 is typically a double skinned structure,
usually made of steel and having an outer wall 2a and
a spaced inner wall 2b.

35

It is clear from the riser configuration shown in Figure 1 that if the top 6 of the riser 2 is not supported and held in position then any force, for example sea currents, exerted on the structure in a direction perpendicular to the plane of the drawing, may cause large displacements creating the risk of interference with other risers and anchor lines employed in the same field. Also, without support from a floating vessel, the weight of the riser 2 may cause unacceptably large bending radii in the riser.

Figure 2 shows a riser configuration in accordance with the present invention. It is similar in overall configuration but the system now includes an articulated joint 7 separating the riser 2 into an upper section 13 and a lower section 14. Both the upper and lower sections 13,14 may be of a double skinned type mentioned above, of steel or other materials, or any other desired type of riser. The articulated joint 7 is preferably located at between 50% and 95% of the water depth below sea level.

The articulated joint 7 allows the configuration of the riser 2 to be modified as shown in Figures 3a and 3b to provide a standby condition in which the riser is installed but can be stabilised and left to await arrival of a production vessel.

In order to stabilise the riser 2 as shown in Figure 3a, an anchor means 8 is attached in the vicinity of the articulated joint 7, which then anchors the entire assembly to the seabed 3 at a location spaced from the attachment of the lower end of the riser 2 to the seabed oil well. A buoyancy member 9 of any desired type is attached to the riser

top 6 and maintains the upper riser section 13 in a nominally vertical position above the anchor means 8.

5 In the alternative configuration shown in Figure 3b, a portion of the lower riser section adjacent the anchor means 8 lies on the seabed, eg. by not placing buoyancy aids 4 on the lower riser section 14 close to the anchor means 8. In this way the weight of the lower riser section 14 itself helps to keep the upper
10 riser section 13 in a nominally vertical position, especially when the anchor means 8 is released from the riser assembly, as described further below with reference to Figures 5, 6 and 6a.

15 This riser assembly is now stabilised against environmental forces such as current. For final connection to a production vessel, the riser top 6 is pulled into the vessel, for example by a winch. As this is done, the riser 2 undergoes a gradual change
20 in configuration as shown in Figure 4 and indicated by reference numbers 10, 11 and 12. Preferably, the wire, cable or chain used to pull in the riser top 6 has a positive substantially vertical load on it during the pulling-in operation and the weight of the
25 anchor means 8 and lower riser section 14 help to maintain this.

Figure 5 shows a detail of one embodiment of the articulated joint 7. The upper riser section 13 is
30 fitted with a connector 15a as known in the industry and which can mate with a counterpart connector 15b fitted to the lower riser section 14. When the two connectors 15a, 15b are connected they allow fluid communication between the interior of the upper and
35 lower riser sections 13, 14.

The articulated joint 7 connects the upper and lower riser sections 13,14 to one another and allows pivoting about an axis 7a which is perpendicular to the plane of the paper in Figure 5.

5

Under the influence of the pulling-in operation shown in Figure 4, as the upper riser section 13 is pulled upwardly, the gap and angle between the mating faces of connectors 15a,15b gradually reduces as both connectors pivot about the axis 7a. In order to assist in the full closure of the connectors 15a,15b, an actuator such as a hydraulic ram 16 may be fitted to assist as shown. Once the angle between the connectors 15a,15b is reduced to zero and the longitudinal axes of both upper and lower riser sections 13,14 are aligned with one another, the connectors 15a,15b mate to achieve a fluid type connection between the upper and lower riser sections 13,14.

20

The anchor means 8 may be configured such that the connector 15a of the upper riser section 13 can be moved vertically in order to engage and disengage directly with a fitting on the anchor means 8 as shown in Figure 5. Upon pulling-in, connector 15a releases from the anchor means 8 and rises upward, allowing pivoting movement about axis 7a as described above. The anchor means 8 remains on the sea floor.

25

Alternatively, the anchor means 8 may be a ballast weight connected to the articulated joint 7 by one or more sections of chain or cable 17 as shown in Figure 6. In this case, the chains or cable 17 are spaced laterally from the hinge point of the articulated joint 7 so as not to interfere with the

30

35

pivotal movement. This displacement is shown in Figure 6a. In this embodiment, upon pulling-in, the ballast weight may be raised up with the whole riser assembly as its weight is overcome by the upward force exerted on the upper riser section 13 until the connectors 15a, 15b have engaged and the top 6 of the upper riser section 13 is secured to the vessel, at which time the anchor means 8 is released from the riser assembly. Alternatively, the anchor means 8 may be released as soon as the pulling-in operation commences.

It will be apparent to a person skilled in the art that a number of modifications to the invention are possible without departing from the scope of the claims. For example, the precise configuration of the articulated joint 7, the actuator 16 and the anchor 8 can be varied as required.

It will be clear from the foregoing that the present invention provides an improved riser system which allows a dynamic riser to be assembled and left in a stable, standby condition ready for connection to a production vessel when it arrives in the field. This significantly reduces the time between arrival of the production vessel and the start of production, with consequent financial savings.

CLAIMS:

1. A riser system for connecting a seabed
installation to a floating vessel, comprising a first
5 conduit for conveying fluid and which is attachable at
a first end to a seabed installation and comprises
connector means at a second end, a second conduit for
conveying fluid and which is attachable at a first end
to a floating vessel and comprises connector means at
10 a second end which is engageable with the connector
means of the first conduit to allow fluid
communication between the first and second conduits,
articulation means joining the first and second
conduits to allow relative rotation therebetween about
15 a pivot axis whereby the first and second conduits are
movable into alignment with one another to allow
mating engagement of the respective connector means
and out of alignment with one another to allow
disengagement of the respective connector means.

20
2. A riser system as claimed in claim 1,
further comprising anchor means operable to anchor the
articulation means adjacent the seabed.

25
3. A riser system as claimed in claim 2,
wherein the anchor means comprises a seabed
installation releasably engageable with the first or
the second conduit.

30
4. A riser system as claimed in claim 2,
wherein the anchor means comprises a ballast weight
releasably attached to the articulation means.

35
5. A riser system as claimed in claim 4,
wherein the ballast weight is secured to the

articulation means at a location displaced from the pivot point.

5 6. A riser system as claimed in any preceding claim, further comprising buoyancy means secured to the first end of the second conduit.

10 7. A riser system as claimed in any preceding claim, further comprising buoyancy means secured to the first conduit between the first and second ends.

15 8. A riser system as claimed in any preceding, further comprising actuator means operable to assist relative rotation of the first and second conduits about the pivot axis.

 9. A riser system as claimed in claim 8, wherein the actuator means comprises a hydraulic ram.

20 10. A riser system as claimed in any preceding claim, wherein the first and second conduits each comprise a double-skinned structure.

25 11. A method of assembling a riser system for connecting a seabed installation with a floating vessel comprising the steps of:

- 30 a) providing first and second conduits each having first and second ends;
- b) providing mating connector means at the respective second ends of the first and second conduits;
- 35 c) providing articulation means joining said first and second conduits adjacent said second ends to allow relative rotation about

a pivot axis whereby the first and second conduits are movable into alignment with one another to allow mating engagement of the respective connector means and out of alignment with another to allow disengagement of the respective connector means; and

- d) attaching the first end of the first conduit to a seabed installation.

12. A method as claimed in claim 11, further comprising the step of anchoring the articulation means adjacent the seabed with anchor means.

13. A method as claimed in claim 12, further comprising the step of providing buoyancy means at the first end of the second conduit to allow the second conduit to float in a substantially vertical position above the anchor means.

14. A method as claimed in claim 13, further comprising the step of raising the first end of the second conduit to overcome said anchor means and to allow pivoting about the pivot axis to bring the connector means into mating engagement, and securing the first end of the second conduit to a floating vessel.

15. A method as claimed in claim 14, wherein the anchoring means is releasably engageable with the first or second conduit or the articulation means and the step of overcoming the anchor means comprises disengaging the respective conduit or the articulation means from the anchor means.

16. A method as claimed in any of claims 11-15,
further comprising dimensioning the first and second
conduits such that the articulation means is located
at between 50% and 95% of the water depth below sea
level.

17. A method as claimed in any of claims 11-16,
further comprising providing buoyancy means on the
first conduit between the first and second ends.

18. A method as claimed in any of claims 11-17,
further comprising providing actuator means operable
to assist relative rotation of the first and second
conduits about the pivot axis.

19. A method of assembling a riser system
substantially as hereinbefore described with reference
to Figures 2-6a.

20. A riser system substantially as hereinbefore
described with reference to Figures 2-6a.



Application No: GB 9721258.3
Claims searched: 1 to 20

Examiner: David Harrison
Date of search: 2 January 1998

Patents Act 1977
Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:

UK Cl (Ed.P): E1F (FAC)

Int Cl (Ed.6): E21B

Other: Online: WPI

Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
A	GB 2296904 A (Victoria Oilfield Development (UK) Limited)	1
A	GB 2206144 A (The British Petroleum Company p.l.c.)	1
A	US 4906137 (Maloberti et al)	1

X Document indicating lack of novelty or inventive step
Y Document indicating lack of inventive step if combined with one or more other documents of same category.
& Member of the same patent family

A Document indicating technological background and/or state of the art.
P Document published on or after the declared priority date but before the filing date of this invention.
E Patent document published on or after, but with priority date earlier than, the filing date of this application.